



Physical Dimensions : mm (inch)

A =  $2.0 \pm 0.2$  (0.079 $\pm$ 0.008)

B =  $1.2 \pm 0.2$  (0.047 $\pm$ 0.008)

C =  $0.9 \pm 0.2$  (0.035 $\pm$ 0.008)

D =  $0.5 \pm 0.3$  (0.020 $\pm$ 0.012)



Electrical Characteristics :

	Value	Unit	Tol.	Test Condition
Z	1000	$\Omega$	$\pm 25\%$	100 MHz / 100 mV
RDC	0.30	$\Omega$	max.	
IDC	1000	mA	max.	

Packing Method:

One Reel = 4,000 pcs

One Box = 200,000 pcs

One Box = 10.7 KG


General information :

Operating Temperature: -55°C to 125°C

Storage Temperature (on Tape & Reel): 40 max, 70% RH

Test conditions of Electrical Properties: 30 max, 70% RH

Typical Impedance Characteristics : HP 4291B



				Multilayer Ferrite Chip Beads	
				P/N	TI 201209 Z102
				Version	N000
Ver.	DESCRIPTION	DATE	BY		
N002	0.12 $\Omega$ / 1500 mA				
N000	0.30 $\Omega$ / 1000 mA				



+886-3-4962286  
www.tecstar.com.tw