


SPECIFICATION FOR APPROVAL



CUSTOMER _____

CUSTOMER'S DWG NO. _____

REVISION NO. _____

CUSTOMER'S PART NO. _____

TECSTAR'S PART NO. TL160808-1R8K _____

QUANTITY _____

PCS _____

ITEM _____

DATE AUG/27/2009 _____

	“ √ ”	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITONAL APPROVED			
REJECTED			



TECSTAR TECHNOLOGY CO., LTD.

NO. 820-1 Kou Shih Rd. Yang Mei Chen


Taoyuan Hsien, Taiwan, R.O.C.

TEL : 886-3-4788701

FAX : 886-3-4788702

www tecstar.com.tw

SPECIFICATION FOR APPROVAL

CUSTOMER:			CUSTOMER'S P/N:		
VENDOR'S P/N:			TL160808-1R8K		
<p>DIMENSION:(m/m)</p> 			A	1.6 ± 0.2	m/m
			B	0.8 ± 0.2	m/m
			C	0.8 ± 0.2	m/m
			D	0.3 ± 0.2	m/m
			E		m/m
			F		m/m
			G		m/m
			H		m/m
			I		m/m
			J		m/m
			K		m/m
			L		m/m
			M		m/m
			N		m/m
O		m/m			
ELECTRICAL REQUIREMENTS			TEST INSTRUMENTS		
L	1.80 ± 10% μH	TEST FREQ.	<input checked="" type="radio"/> HP 4338A MILLIOHMMETER <input type="radio"/> HP 4195A NETWORK/SPECTRUM ANALYZER <input type="radio"/> HP 4284A BIAS CURRENT SOURCE <input type="radio"/> HP 4285A PRECISION LCR METER <input type="radio"/> HP 4286A PRECISION LCR METER <input checked="" type="radio"/> HP 4291B RF IMPEDANCE /MATERIAL ANALYZER <input type="radio"/> HP 6632A DC POWER SUPPLY		
Q	35 MIN.	TEST FREQ.			
Srf	55 MHz MIN.	TEST FREQ.			
Rdc	0.95 OHM. MAX.	TEST FREQ.			
Idc	25 mA MAX.	TEST FREQ.			
DRAWN BY			CHECKED BY		APPROVED BY
Juli Wang			John Chuang		Lionel Lin


TEST DATA

CUSTOMER:							
CUSTOMER'S P/N:						SERIES NO:	TL2441
VENDOR'S P/N:		TL160808-1R8K				DATE:	27-AUG-2009
MEAS	A	B	C	D	L	Q	Rdc
ITEM	(m/m)	(m/m)	(m/m)	(m/m)	(μ H)		(Ω)
SPEC	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2	$1.80 \pm 10\%$	35 MIN.	0.95 MAX.
TEST FREQ.					10MHz	10MHz	
1	1.61	0.80	0.81	0.30	1.82	66.8	0.498
2	1.60	0.82	0.79	0.29	1.80	67.5	0.514
3	1.62	0.81	0.80	0.32	1.87	69.4	0.509
4	1.59	0.80	0.79	0.30	1.80	64.9	0.477
5	1.60	0.79	0.81	0.29	1.75	66.6	0.519
6	1.59	0.80	0.79	0.31	1.85	67.2	0.482
7	1.62	0.81	0.80	0.32	1.82	66.8	0.518
8	1.60	0.79	0.79	0.30	1.80	67.6	0.502
9	1.63	0.80	0.80	0.29	1.83	69.5	0.482
10	1.60	0.79	0.81	0.30	1.81	65.5	0.516
AVG.	1.61	0.80	0.80	0.30	1.82	67.2	0.502
R	0.04	0.03	0.02	0.03	0.12	4.6	0.042
DRAWN BY			CHECKED BY			APPROVED BY	
Juli Wang			John Chuang			Lionel Lin	


TYPICAL ELECTRICAL CHARACTERISTICS CURVE

TL160808 Type


Inductance VS. Frequency




Impedance VS. Frequency



Inductance VS. Temperature




Q VS. Frequency




RELIABILITY TEST

Item	Performance	Test condition
Operating temperature range	-55 °C to + 125 °C	
Storage temperature and umidity ranges	40 °C MAX., 70% RH MAX.	
Soldering heat resistance	The chip shall not be cracks. More than 75% of terminal electrode shall be covered with solder.	Preheat: 150 °C, 60 seconds Solder temperature : 260 ± 5 °C Flux: Rosin Dip time: 10 ± 1 seconds




Solderability	More than 90% of the terminal electrode shall be covered with new solder.	Preheat: 150 °C, 60 seconds Solder temperature: 245 ± 5 °C Flux: Rosin Dip time: 4 ± 1 seconds
---------------	---	---



Recommended Soldering Conditions

(REFLOW TEMPERATURE PROFILE) Lead-Free


A	$260 \pm 5^{\circ}\text{C}$
B	$230 \pm 5^{\circ}\text{C}$
C	$30 \pm 10 \text{ sec}$
D	150°C
E	180°C
F	$90 \pm 30 \text{ sec}$



RELIABILITY TEST

Terminal strength


The terminal electrode and the body shall not be damaged by the forces applied on the right conditions.



Type	P (kgf)	Time (s)
T□100505	0.3	
T□160808	0.5	
T□201209	0.6	
T□201212	0.8	
T□321611	1.0	
T□322513	1.0	30 ± 5
T□451616	1.0	
T□453215	1.5	
TA3216M4	0.5	





Bending strength

The body shall not be damaged by the forces applied on the right conditions.




Type	A (mm)	P (kgf)
T□160808	1.0	0.5
T□201209	1.4	1.0
T□201212	1.4	1.2
T□321611	2.0	2.0
T□322513	2.0	2.5
T□451616	2.5	2.5
T□453215	2.7	2.5
TA3216M4	1.4	1.0

RELIABILITY TEST


Item	Performance	Test condition
High temperature resistance	Appearance : Ferrite shall not be damaged. Inductance : Within $\pm 10\%$ of the initial value. Q: Within $\pm 30\%$ of the initial value.	Temperature: $85\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 
Humidity resistance	Appearance: Ferrite shall not be damaged. Inductance: Within $\pm 10\%$ of the initial value Q: Within $\pm 30\%$ of the initial value.	Humidity: 90 to 95% RH Temperature: $40\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 
Thermal Shock	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Inductance: Within $\pm 10\%$ of the initial value Q: Within $\pm 30\%$ of the initial value.	Temperature: -40°C , $+85^{\circ}\text{C}$, kept stabilized for 30 minutes each Cycle: 100 cycles Measurement: After placing for 24 hours min 
Low temperature storage life test	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Inductance: Within $\pm 10\%$ of the initial value. Q: Within $\pm 30\%$ of the initial value.	Temperature: $-40\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 

PACKAGING

● Tape dimensions and packaging quantities



Carrier tape material: paper




material: Paper (Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
100505	0.62	1.12	8	2	0.60	10000
160808	1.10	1.90	8	4	0.95	4000
201209	1.50	2.30	8	4	0.95	4000
material: Polystyrene (Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
160808	1.01	1.80	8	4	1.02	4000
201209	1.42	2.25	8	4	1.04	4000
201212	1.50	2.35	8	4	1.45	2000
321611	1.88	3.50	8	4	1.27	3000

● Reel dimensions

Material: Paper, Plastic

Dimensions in mm



TYPE	8mm	12mm
A	178±2	178±2
B	21.0±0.8	21.0±0.8
C	13.0±0.8	13.0±0.8
G	10.0	14.0
N	75	75
T	12.5	16.5

