


# SPECIFICATION FOR APPROVAL



CUSTOMER

---

CUSTOMER'S DWG NO.

REVISION NO.

---

CUSTOMER'S PART NO.

---

TECSTAR'S PART NO.

TL160808-47NM

---

QUANTITY

PCS

---

ITEM

DATE

SEP/03/2009

---

	“√”	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITONAL APPROVED			
REJECTED			



## TECSTAR TECHNOLOGY CO., LTD.

NO. 820-1 Kou Shih Rd. Yang Mei Chen

Taoyuan Hsien, Taiwan, R.O.C.

TEL : 886-3-4788701

FAX : 886-3-4788702

www tecstar.com.tw

# SPECIFICATION FOR APPROVAL

CUSTOMER:				CUSTOMER'S P/N:				
VENDOR'S P/N:				TL160808-47NM				
<p>DIMENSION:(m/m)</p>				A	1.6 ± 0.2	m/m		
				B	0.8 ± 0.2	m/m		
				C	0.8 ± 0.2	m/m		
				D	0.3 ± 0.2	m/m		
				E		m/m		
				F		m/m		
				G		m/m		
				H		m/m		
				I		m/m		
				J		m/m		
				K		m/m		
				L		m/m		
				M		m/m		
				N		m/m		
O		m/m						
<b>ELECTRICAL REQUIREMENTS</b>				<b>TEST INSTRUMENTS</b>				
L	47 ± 20%	nH	TEST FREQ.	<input checked="" type="radio"/> HP 4338A MILLIOHMMETER <input type="radio"/> HP 4195A NETWORK/SPECTRUM ANALYZER <input type="radio"/> HP 4284A BIAS CURRENT SOURCE <input type="radio"/> HP 4285A PRECISION LCR METER <input type="radio"/> HP 4286A PRECISION LCR METER <input checked="" type="radio"/> HP 4291B RF IMPEDANCE /MATERIAL ANALYZER <input type="radio"/> HP 6632A DC POWER SUPPLY			50MHz/100mV	
Q	10	MIN.	TEST FREQ.	50MHz/100mV				
Srf	260	MHz	TEST FREQ.	MHz				
Rdc	0.30	OHM.	TEST FREQ.	MHz				
Idc	50	mA	TEST FREQ.	MHz				
DRAWN BY			CHECKED BY			APPROVED BY		
Juli Wang			John Chuang			Lionel Lin		


# TEST DATA

CUSTOMER:							
CUSTOMER'S P/N:						SERIES NO:	TL2589
VENDOR'S P/N:		TL160808-47NM				DATE:	13-SEP-2009
MEAS	A	B	C	D	L	Q	Rdc
ITEM	(m/m)	(m/m)	(m/m)	(m/m)	(nH)		( $\Omega$ )
SPEC	$1.6 \pm 0.2$	$0.8 \pm 0.2$	$0.8 \pm 0.2$	$0.3 \pm 0.2$	$47 \pm 20\%$	10 MIN.	0.30 MAX.
TEST FREQ.					50MHz	50MHz	
1	1.63	0.82	0.81	0.32	48.8	48.6	0.076
2	1.61	0.80	0.83	0.30	46.6	45.7	0.066
3	1.62	0.83	0.84	0.31	45.9	46.4	0.070
4	1.62	0.80	0.82	0.29	46.9	44.0	0.077
5	1.64	0.81	0.83	0.31	47.0	45.5	0.072
6	1.63	0.81	0.83	0.32	45.4	47.3	0.073
7	1.64	0.82	0.82	0.33	46.3	49.0	0.075
8	1.65	0.83	0.81	0.29	44.6	46.6	0.070
9	1.62	0.80	0.81	0.32	47.7	50.3	0.073
10	1.61	0.81	0.82	0.31	47.2	51.2	0.069
AVG.	1.63	0.81	0.82	0.31	46.6	47.5	0.072
R	0.04	0.03	0.03	0.04	4.2	7.3	0.011
DRAWN BY			CHECKED BY			APPROVED BY	
Juli Wang			John Chuang			Lionel Lin	


# TYPICAL ELECTRICAL CHARACTERISTICS CURVE

TL160808 Type


Inductance VS. Frequency




Impedance VS. Frequency



Inductance VS. Temperature




Q VS. Frequency




# RELIABILITY TEST

Item	Performance	Test condition
Operating temperature range	-55 °C to + 125 °C	
Storage temperature and umidity ranges	40 °C MAX., 70% RH MAX.	
Soldering heat resistance	The chip shall not be cracks. More than 75% of terminal electrode shall be covered with solder.	Preheat: 150 °C, 60 seconds Solder temperature : 260 ± 5 °C Flux: Rosin Dip time: 10 ± 1 seconds




Solderability	More than 90% of the terminal electrode shall be covered with new solder.	Preheat: 150 °C, 60 seconds Solder temperature: 245 ± 5 °C Flux: Rosin Dip time: 4 ± 1 seconds
---------------	---	---



## Recommended Soldering Conditions

(REFLOW TEMPERATURE PROFILE) Lead-Free


A	$260 \pm 5^{\circ}\text{C}$
B	$230 \pm 5^{\circ}\text{C}$
C	$30 \pm 10 \text{ sec}$
D	$150^{\circ}\text{C}$
E	$180^{\circ}\text{C}$
F	$90 \pm 30 \text{ sec}$



# RELIABILITY TEST

Terminal strength


The terminal electrode and the body shall not be damaged by the forces applied on the right conditions.



Type	P (kgf)	Time (s)
T□100505	0.3	
T□160808	0.5	
T□201209	0.6	
T□201212	0.8	
T□321611	1.0	
T□322513	1.0	30 ± 5
T□451616	1.0	
T□453215	1.5	
TA3216M4	0.5	





Bending strength

The body shall not be damaged by the forces applied on the right conditions.




Type	A (mm)	P (kgf)
T□160808	1.0	0.5
T□201209	1.4	1.0
T□201212	1.4	1.2
T□321611	2.0	2.0
T□322513	2.0	2.5
T□451616	2.5	2.5
T□453215	2.7	2.5
TA3216M4	1.4	1.0

# RELIABILITY TEST

Item	Performance	Test condition
High temperature resistance	Appearance : Ferrite shall not be damaged. Inductance : Within±10% of the initial value. Q: Within±30% of the initial value.	Temperature: 85±2°C Testing time: 1008±12 hours Measurement: After placing for 24 hours min 
Humidity resistance	Appearance: Ferrite shall not be damaged. Inductance: Within±10% of the initial value Q: Within±30 % of the initial value.	Humidity: 90 to 95% RH Temperature: 40±2°C Testing time: 1008±12 hours Measurement: After placing for 24 hours min 
Thermal Shock	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed.  Inductance: Within±10% of the initial value Q: Within±30% of the initial value.	Temperature: -40°C, +85°C, kept stabilized for 30 minutes each Cycle: 100 cycles Measurement: After placing for 24 hours min 
Low temperature storage life test	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Inductance: Within±10% of the initial value. Q: Within±30% of the initial value.	Temperature: -40±2°C Testing time: 1008±12 hours Measurement: After placing for 24 hours min 

# PACKAGING


- Tape dimensions and packaging quantities



material: Paper ( Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
100505	0.62	1.12	8	2	0.60	10000
160808	1.10	1.90	8	4	0.95	4000
201209	1.50	2.30	8	4	0.95	4000
material: Polystyrene ( Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
160808	1.01	1.80	8	4	1.02	4000
201209	1.42	2.25	8	4	1.04	4000
201212	1.50	2.35	8	4	1.45	2000
321611	1.88	3.50	8	4	1.27	3000

- Reel dimensions

Material: Paper, Plastic



Dimensions in mm

TYPE	8mm	12mm
A	178±2	178±2
B	21.0±0.8	21.0±0.8
C	13.0±0.8	13.0±0.8
G	10.0	14.0
N	75	75
T	12.5	16.5

