


SPECIFICATION FOR APPROVAL



CUSTOMER

CUSTOMER'S DWG NO.

REVISION NO.

CUSTOMER'S PART NO.

TECSTAR'S PART NO.

TL201209-R18K

QUANTITY

PCS

ITEM

DATE

SEP/03/2009


	“√”	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITONAL APPROVED			
REJECTED			



TECSTAR TECHNOLOGY CO., LTD.

NO. 820-1 Kou Shih Rd. Yang Mei Chen
Taoyuan Hsien, Taiwan, R.O.C.
TEL : 886-3-4788701
FAX : 886-3-4788702
www tecstar.com.tw

SPECIFICATION FOR APPROVAL

CUSTOMER:		CUSTOMER'S P/N:			
VENDOR'S P/N:		TL201209-R18K			
<p>DIMENSION:(m/m)</p> 		A	2.0 ± 0.2	m/m	
		B	1.2 ± 0.2	m/m	
		C	0.9 ± 0.2	m/m	
		D	0.5 ± 0.3	m/m	
		E		m/m	
		F		m/m	
		G		m/m	
		H		m/m	
		I		m/m	
		J		m/m	
		K		m/m	
		L		m/m	
		M		m/m	
		N		m/m	
O		m/m			
ELECTRICAL REQUIREMENTS		TEST INSTRUMENTS			
L	180 ± 10% nH	TEST FREQ.	<ul style="list-style-type: none"> ● HP 4338A MILLIOHMMETER ○ HP 4195A NETWORK/SPECTRUM ANALYZER ○ HP 4284A BIAS CURRENT SOURCE ○ HP 4285A PRECISION LCR METER ○ HP 4286A PRECISION LCR METER ● HP 4291B RF IMPEDANCE /MATERIAL ANALYZER ○ HP 6632A DC POWER SUPPLY 		
Q	20 MIN.	TEST FREQ.			25MHz/100mV
Srf	185 MHz MIN.	TEST FREQ.			MHz
Rdc	0.40 OHM. MAX.	TEST FREQ.			MHz
Idc	250 mA MAX.	TEST FREQ.			MHz
DRAWN BY		CHECKED BY		APPROVED BY	
Juli Wang		John Chuang		Lionel Lin	


TEST DATA

CUSTOMER:							
CUSTOMER'S P/N:						SERIES NO:	TL3058
VENDOR'S P/N:		TL201209-R18K				DATE:	03-SEP-2009
MEAS	A	B	C	D	L	Q	Rdc
ITEM	(m/m)	(m/m)	(m/m)	(m/m)	(nH)		(Ω)
SPEC	2.0 ± 0.2	1.2 ± 0.2	0.9 ± 0.2	0.5 ± 0.3	$180 \pm 10\%$	20 MIN.	0.40 MAX.
TEST FREQ.					25 MHz	25 MHz	
1	2.02	1.25	0.89	0.52	181.8	50.1	0.059
2	2.01	1.22	0.90	0.50	187.9	54.3	0.056
3	2.05	1.20	0.88	0.48	178.7	50.5	0.059
4	2.01	1.23	0.89	0.52	179.9	47.6	0.057
5	2.03	1.21	0.90	0.50	186.0	54.8	0.058
6	2.04	1.24	0.91	0.51	178.3	47.2	0.061
7	2.01	1.20	0.89	0.53	172.1	47.5	0.056
8	2.02	1.23	0.88	0.52	175.3	49.1	0.059
9	2.03	1.22	0.90	0.49	177.7	51.3	0.057
10	2.04	1.21	0.88	0.52	174.2	46.2	0.056
AVG.	2.03	1.22	0.89	0.51	179.2	49.9	0.058
R	0.04	0.05	0.03	0.05	15.8	8.6	0.005
DRAWN BY			CHECKED BY			APPROVED BY	
Juli Wang			John Chuang			Lionel Lin	


TYPICAL ELECTRICAL CHARACTERISTICS CURVE

TL2012 Type


Inductance VS. Frequency




Impedance VS. Frequency



Inductance VS. Temperature





Q VS. Frequency



RELIABILITY TEST


Item	Performance	Test condition
Operating temperature range	-55 °C to + 125 °C	
Storage temperature and umidity ranges	40 °C MAX., 70% RH MAX.	
Soldering heat resistance	The chip shall not be cracks. More than 75% of terminal electrode shall be covered with solder.	Preheat: 150 °C, 60 seconds Solder temperature : 260 ± 5 °C Flux: Rosin Dip time: 10 ± 1 seconds
Solderability	More than 90% of the terminal electrode shall be covered with new solder.	Preheat: 150 °C, 60 seconds Solder temperature: 245 ± 5 °C Flux: Rosin Dip time: 4 ± 1 seconds



Recommended Soldering Conditions

(REFLOW TEMPERATURE PROFILE) Lead-Free


A	$260 \pm 5^{\circ}\text{C}$
B	$230 \pm 5^{\circ}\text{C}$
C	$30 \pm 10 \text{ sec}$
D	150°C
E	180°C
F	$90 \pm 30 \text{ sec}$



RELIABILITY TEST

Terminal strength


The terminal electrode and the body shall not be damaged by the forces applied on the right conditions.



Type	P (kgf)	Time (s)
T□100505	0.3	
T□160808	0.5	
T□201209	0.6	
T□201212	0.8	
T□321611	1.0	
T□322513	1.0	30 ± 5
T□451616	1.0	
T□453215	1.5	
TA3216M4	0.5	





Bending strength

The body shall not be damaged by the forces applied on the right conditions.




Type	A (mm)	P (kgf)
T□160808	1.0	0.5
T□201209	1.4	1.0
T□201212	1.4	1.2
T□321611	2.0	2.0
T□322513	2.0	2.5
T□451616	2.5	2.5
T□453215	2.7	2.5
TA3216M4	1.4	1.0

RELIABILITY TEST

Item	Performance	Test condition
High temperature resistance	Appearance : Ferrite shall not be damaged. Inductance : Within±10% of the initial value. Q: Within±30% of the initial value.	Temperature: $85\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 
Humidity resistance	Appearance: Ferrite shall not be damaged. Inductance: Within±10% of the initial value Q: Within±30 % of the initial value.	Humidity: 90 to 95% RH Temperature: $40\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 
Thermal Shock	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Inductance: Within±10% of the initial value Q: Within±30% of the initial value.	Temperature: -40°C , $+85^{\circ}\text{C}$, kept stabilized for 30 minutes each Cycle: 100 cycles Measurement: After placing for 24 hours min 
Low temperature storage life test	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Inductance: Within±10% of the initial value. Q: Within±30% of the initial value.	Temperature: $-40\pm 2^{\circ}\text{C}$ Testing time: 1008 ± 12 hours Measurement: After placing for 24 hours min 

PACKAGING


- Tape dimensions and packaging quantities



material: Paper (Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
100505	0.62	1.12	8	2	0.60	10000
160808	1.10	1.90	8	4	0.95	4000
201209	1.50	2.30	8	4	0.95	4000
material: Polystyrene (Dimensions in mm)						
TYPE	A	B	W	P	T	CHIPS / REEL
160808	1.01	1.80	8	4	1.02	4000
201209	1.42	2.25	8	4	1.04	4000
201212	1.50	2.35	8	4	1.45	2000
321611	1.88	3.50	8	4	1.27	3000

- Reel dimensions

Material: Paper, Plastic



Dimensions in mm

TYPE	8mm	12mm
A	178±2	178±2
B	21.0±0.8	21.0±0.8
C	13.0±0.8	13.0±0.8
G	10.0	14.0
N	75	75
T	12.5	16.5

